

BOILER CONDENSATE TREATMENT

FlowEco 6685 is a high performance, formulated blend of neutralising amines designed to give maximum corrosion protection for condensate systems. Protection is given no matter if the condensate system is long or short.

BENEFITS

- Rapid acting. Raise pH immediately.
- Low dose rates, cost effective.
- Application based on an extended field experience.

FlowEco 6685

GENERAL SPECIFICATIONS

Appearance	: Clear, pale yellow liquid
pH (as supplied)	: 11.5 – 12.5
Specific Gravity	: .95 – 1.05
Solubility in Water	: Miscible in all proportions

TREATMENT AND DOSAGE REQUIREMENT

FlowEco 6685 is dosed into the feed water using a chemical dosing pump. The optimum treatment level depends on a number of conditions including the chemical characteristics of the feed water. The actual dosage rate will be determined by our engineer after careful consideration of the system. Field experience and studies has shown that **FlowEco 6685** is considerably more effective than any other compatible corrosion inhibitor in the market.

PACKAGING

FlowEco 6685 is supplied in 25 kg drums.

FlowEco 6685

SAFETY

This product is toxic by ingestion and must be handled with great care. Do not use or store near foodstuffs, areas where food is stored, prepared or eaten, animal feeds, fertilizers or water supplies. Avoid ingestion and always wear P.V.C. gloves when handling the product or solution containing the product. Always wash hands after use. Wash out empty container and dispose of safely. Do not re-use containers. Keep only in the original container. Should this material be accidentally swallowed, give copious water to drink and seek immediate medical attention showing the product label.

This product is moderately flammable, and should be used and stored away from all sources of ignition. As with all chemicals it should be handled with care. Skin and eye contact should be avoided and overalls, rubber / PVC gloves and goggles should be worn when handling the product. Please refer to the Material Safety Data Sheet for further details.

FlowEco 6685

GENERAL SAFETY INSTRUCTIONS:

- Ensure that the operator is fully informed and familiar with the use of the product.
- Avoid ingestion of the product by mouth and nose. To eliminate the possibility of accidental ingestion, operator should never eat, drink or smoke when using chemicals. In addition, protective clothing should be removed, and the hands washed prior to eating, drinking or smoking.
- Store in the original containers and ensure that the cap is always secure.
- Do not store in temperatures above 40°C or below 0°C for extended periods.
- Do not stack more than two high for prolonged periods.
- Avoid storing near direct heat and in direct sunlight.
- Store out of the reach of children and away from.